



Powered by

Kubota®



25KVA Technical Specification

Generator Model		PEKL-25	
KVA/KW (Prime)		25KVA / 20KW	
KVA/KW (Standby)		27.5KVA / 22KW	
Frequency / RPM		50 Hz / 1500	
Voltage / No. of Phase		415 / 3	
Rated Current (Amps)		34.75	
Over Load Capacity		10 % over Load for 1 Hours in each 12 Hour of Operation	
Fuel Tank Capacity (liters)		100	
Acoustic Enclosure Dimensions L X W X H (mm) including Silencer		1900 x 900 x 1350	
Gross Weight (Kg)(Approx)		950	
Engine			
Engine Model		G25A-II	
No. Of Cylinder		3 Cylinder	
Engine Cooling Type		Water Cooled	
Bore		98 mm	
Stroke		122 mm	
Swept volume		2.76 litre	
Aspiration		Naturally Aspirated	
Maximum/Rated Power @ rpm		35.51 HP	
Max. operational speed		1500 RPM	
Engine Maximum air flow		117 kg/hr.	
Compression Ratio		17.5:1	
Lub Oil Sump Capacity		6 litre	
Fuel injection Pump - Supplier		Bosch	
Fuel injector - Supplier		Bosch	
Starter Motor		2.5 KW	
Charging Alternator		35AMP	
Stop Control		Solenoid	
Air Cleaner Type		Dry	
Heat Rejection Rate		19.5 KW/hr	
System Pressure		0.9 Bar	
Electrical System		12 V	
NO. of Battery		1	
Battery Capacity		88 AH	
Alternator			
Alternator Make		Stamford	Leroy-somer
Alternator Model		S0L2-M1	LSAP 42.3 B
Volage		415 Vol / 230 Vol	
Frequency		50Hz	
Class of Insulation		Class H	
Voltage Regulation		± 1%	
Power Factor		0.8	
Pole		4 Pole	
Voltage Regulation		AVR (Automatic Voltage Regulator)	
IP Rating		IP 23	
Control Panel			
Battery Charger		12 VDC, Automatic Battery Charger	
Controller		Deep Sea 4520 MK II	

DG CONTROL PANEL

► Operating Features

- Microprocessor based digital controller
- Accurate LCD display
- Local Start/Stop
- Remote Start/Stop
- Generator breaker control
- Easily Accessible through Fascia
- Flexibility for selecting Manual, Auto operations
- Easily Convertible AMF by giving Mains Fail Signal

► Metering

Engine Parameters:

- Engine Speed
- Lube Oil pressure
- Coolant temperature
- Engine Running Hour
- Engine Battery voltage
- Running status
- Fuel level in Percentage
- Event Log with date and time

Electrical Parameter

- Generator Voltage (Ph-Ph)
- Generator Voltage (Ph-N)
- Generator Current (R,Y,B)
- Generator Apparent power (kVA)
- Generator active power(kW)
- Generator reactive power (kVAr)
- Generator Power Factor
- Generator Frequency (Hz)
- Cumulative Power Consumption in kWh
- Cumulative Power Consumption in kVAh
- Cumulative Power Consumption in kVArh
- Control Supply Voltage

► Protection

Engine

- High Water Temperature
- Low oil pressure
- Low Fuel Level
- Over Speed
- Engine Fails to Start

Electrical

- Generator under Voltage (ANSI-27)
- Generator over Voltage (ANSI-59)
- Generator under Frequency (ANSI-81L)
- Generator over Frequency (ANSI-81H)
- Generator over Current (ANSI-51)
- Control Supply under Voltage
- Control Supply over Voltage
- Phase Reversal
- Unbalanced Load

► Controller

The DSE 4520 MKII Is A Compact Auto Mains (utility) Failure Control Module That Has Been Developed To Provide An Outstanding Range Of Features Within A Compact Enclosure.

The Module Can Be Configured For Use As An Auto Start Control Module.



► Controller Feature

- User-friendly interface and backlite full graphics LCD
- Battery voltage monitoring & reverse protection to aux supply
- 7/9 configurable analogue/digital inputs
- Auto, Manual and Remote Start/Stop Operation
- Island Operation
- Automatic Mains Failure Function
- CANbus Engine interface for communication
- Log with latest 100 events
- Fully configurable via PC using USB, RS485 communication
- DC Battery supply voltage range 8 to 32V
- -20 to 65 °C operating temperature range
- Ip65 Protection class with gasket
- LCD alarm indication
- Power save mode
- 7 configurable Digital output

► Electrical Specification

- Supply Voltage Range: Nominal Voltage - 12/24 V DC
- Cranking drop out period: 50 ms
- Maximum reverse voltage protection: -32 V DC
- Measurement accuracy (battery voltage): $\pm 1\%$ Full scale
- Resolution: 0.1 V
- Maximum current consumption ~ 200 mA
- Measurement accuracy (battery voltage) - $\pm 1\%$ full scale

► Environmental Specification

- Operating Temp: -20 to 65°C in compliance with 60068-2-1, 2
- Vibration: 2G in X, Y and Z axes for 8 to 500Hz in compliance with IEC 60068-2-6
- Shock: 15 g for 11 ms in compliance with IEC 60068-2-27
- Humidity: 0 to 95% RH in compliance with IEC 60068-2-78
- Protection Degree: IP65 Protection class with gasket in compliance with IEC60529
- EMI/EMC in compliance with IEC 61000-6-2, 4

► Approvals

- CE Compliant
- UL/cUL Recognized to UL/ulc6200:2019 1st edition



PERFECT[®]
SOLVING YOUR POWER NEEDS...

60+

of
Legacy

5GW+

of Power
Delivered



Globally
Certified

800+

Employees
Across the Globe

24*,000 sq.ft

Manufacturing Unit

2,00,000+

Power Generators Supplied

35+

Countries Powering Global
Success



Perfect House Pvt. Ltd.

2nd Floor, 99C Kavya Aura, Next to Rosewood Hotel, Tardeo, Mumbai –
400034, India

Contact No: +9122-62611900/907

✉ exports@perfectgenset.com

Factories

Plot no. M-7, J-2/5, J-2/6, J-10,

Additional MIDC, Satara -415004, India