



Uninterrupted Power, Unmatched Reliability with Perfect Generators powered by

VE COMMERCIAL VEHICLES
A VOLVO GROUP AND EICHER MOTORS JOINT VENTURE

&

**VOLVO
PENTA**



PERFECT SUPER SILENT GENERATING SETS POWERED BY VOLVO EICHER ENGINE

82.5 KVA SPECIFICATIONS (VOLVO EICHER)

D.G. Set	Generating Set Model	PVE 82.5	
	kVA /KW (Prime)	82.5/66	
	kVA /KW (Standby)	91/73	
	Frequency / RPM	50 Hz /60 Hz , 1500 / 1800	
	Voltage / no. of Phase	415 / 3	
	Power Factor	0.8	
	Rated Current (Amps)	115	
	Over Load Capacity	10 % over Load for 1 Hours in each 12 Hour of Operation	
	Fuel Tank Capacity (liters)	145	
	Acoustic Enclosure Dimensions L X W X H (mm) including Silencer	3100 X 1080 X 1575	
	Gross Weight (Kg)(Approx)	1700	
Diesel Engine	Engine Make	VOLVO EICHER (A Volvo Group and Eicher Motor Joint Venture)	
	Engine Model	EE683TCI	
	Engine Power (bhp)	105	
	No. of Cylinders	6	
	Fuel Consumption (Lit/ Hr) @100% Load	14.5	
	Fuel Consumption (Lit/ Hr) @75% Load	10.3	
	Cooling system	Liquid Cooled	
	Type of governor	Mechanical	
	Aspiration	TURBO CHARGED INTERCOOLED	
	Lube oil sump capacity (Ltrs.)	16	
	Recommended Service Interval for Genset.	500 Hours / 12 Month whichever is earlier	
	Coolant Capacity - UOM as Litres	20	
	Recommended Coolant	Ethylene glycol base concentrate ideal mixing ratio of water to antifreeze is 50:50	
	Electrical System (12V /24V)	12V	
	NO. of Battery	1	
Battery Capacity	120 AH		
Alternator	Alternator Make	Stamford	Leroy-somer
	Alternator Model	UCI224G	LSAP 44.3 B2
	Volage	415 Vol / 230 Vol	
	Frequency	50Hz	
	Class of Insulation	Class H	
	Voltage Regulation	± 1%	
	Power Factor	0.8	
	Pole	4 Pole	
	Voltage Regulation	AVR (Automatic Voltage Regulator)	
IP Rating	IP 23		
Panel	Battery Charger	12 VDC, Automatic Battery Charger	
	Controller	Deep Sea 4520 MK II	

Notes:

- Specifications and Dimensions are subjected to change without prior notice.
- Data is on NTP conditions as per ISO 3046.
- ±5% production tolerance is applicable as per ISO3046. Fuel consumption is based on diesel fuel with a specific gravity of 0.85 and confirming to BS 2869, Class A2) and standard alternator efficiency. The fuel consumption may vary depending upon the alternator.

DG CONTROL PANEL

▶ Operating Features

- Microprocessor based digital controller
- Accurate LCD display
- Local Start/Stop
- Remote Start/Stop
- Generator breaker control
- Easily Accessible through Fascia
- Flexibility for selecting Manual, Auto operations
- Easily Convertible AMF by giving Mains Fail Signal

▶ Metering

Engine Parameters:

- Engine Speed
- Lube Oil pressure
- Coolant temperature
- Engine Running Hour
- Engine Battery voltage
- Running status
- Fuel level in Percentage
- Event Log with date and time

Electrical Parameter

- Generator Voltage (Ph-Ph)
- Generator Voltage (Ph-N)
- Generator Current (R,Y,B)
- Generator Apparent power (kVA)
- Generator active power(kW)
- Generator reactive power (kVAr)
- Generator Power Factor
- Generator Frequency (Hz)
- Cumulative Power Consumption in kWh
- Cumulative Power Consumption in kVAh
- Cumulative Power Consumption in kVArh
- Control Supply Voltage

▶ Protection

Engine

- High Water Temperature
- Low oil pressure
- Low Fuel Level
- Over Speed
- Engine Fails to Start

Electrical

- Generator under Voltage (ANSI-27)
- Generator over Voltage (ANSI-59)
- Generator under Frequency (ANSI-81L)
- Generator over Frequency (ANSI-81H)
- Generator over Current (ANSI-51)
- Control Supply under Voltage
- Control Supply over Voltage
- Phase Reversal
- Unbalanced Load

▶ Controller

The DSE 4520 MKII Is A Compact Auto Mains (utility) Failure Control Module That Has Been Developed To Provide An Outstanding Range Of Features Within A Compact Enclosure.

The Module Can Be Configured For Use As An Auto Start Control Module.



▶ Controller Feature

- User-friendly interface and backlite full graphics LCD
- Battery voltage monitoring & reverse protection to aux supply
- 7/9 configurable analogue/digital inputs
- Auto, Manual and Remote Start/Stop Operation
- Island Operation
- Automatic Mains Failure Function
- CANbus Engine interface for communication
- Log with latest 100 events
- Fully configurable via PC using USB, RS485 communication
- DC Battery supply voltage range 8 to 32V
- -20 to 65 °C operating temperature range
- Ip65 Protection class with gasket
- LCD alarm indication
- Power save mode
- 7 configurable Digital output

▶ Electrical Specification

- Supply Voltage Range: Nominal Voltage - 12/24 V DC
- Cranking drop out period: 50 ms
- Maximum reverse voltage protection: -32 V DC
- Measurement accuracy (battery voltage): ± 1 % Full scale
- Resolution: 0.1 V
- Maximum current consumption ~ 200 mA
- Measurement accuracy (battery voltage) - ± 1 % full scale

▶ Environmental Specification

- Operating Temp: -20 to 65°C in compliance with 60068-2-1, 2
- Vibration: 2G in X, Y and Z axes for 8 to 500Hz in compliance with IEC 60068-2-6
- Shock: 15 g for 11 ms in compliance with IEC 60068-2-27
- Humidity: 0 to 95% RH in compliance with IEC 60068-2-78
- Protection Degree: IP65 Protection class with gasket in compliance with IEC60529
- EMI/EMC in compliance with IEC 61000-6-2, 4

▶ Approvals

- CE Compliant
- UL/cUL Recognized to UL/ulc6200:2019 1st edition



60+
of
Legacy

5GW+
of Power
Delivered

**Globally
Certified**

800+
Employees
Across the Globe

24,000 sq.ft
Manufacturing Unit

200,000+
Power Generators Supplied

35+
Countries Powering Global
Success



Perfect House Pvt. Ltd.

2nd Floor, 99C Kavya Aura, Next to Rosewood Hotel, Tardeo,
Mumbai – 400034, India

Contact No: +9122-62611900/907

✉ exports@perfectgenset.com

Factories

Plot no. M-7, J-2/5, J-2/6, J-10,
Additional MIDC, Satara -415004, India